



WL50

High-performance water dispenser

The WL50 is equipped with premium filtration and an integrated in-tank LED UV, making it ideal for high-traffic environments.

Advanced technology:



High performance filtration Configured with 5-stage reverse osmosis filtration or 4-stage carbon filtration.



In-tank LED UV
In-tank LED UV technology helps maintain system cleanliness.



Surface protection technology*
Key surfaces are infused with surface protection technology, inhibiting the growth of odor and stain-causing microbes.



Large capacity hot tank
Equipped with 1.1 gallon stainless steel hot tank.



Number of users: 50+

*Surface protection technology protects surfaces from odor and stain-causing microbes. It does not protect users against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

Features

Reverse osmosis with mineral add back or 4-stage carbon filtration

Quick-change filtration system allows for easier filter changes and fewer fittings

Gravity-fed stainless steel storage tank

Patented recirculating cold water system pumps water by the in-tank LED UV light every 15 minutes to re-chill and maintain fresh, great tasting water

Fast cold water dispense rate is double the rate of a traditional cooler

Equipped with internal air filter to minimize introduction of contaminants

Float-style leak detection system provides peace of mind and reduces the risk of leaks

Illuminated display and dispense area turns blue when dispensing cold water and turns red when dispensing hot for a better user experience

Temperature options

cold hot



Technical specifications

Dimensions

11.8" (W) x 50.3" (H) x 17.2" (D)

Dispense area height

11"

Weight

59 lbs

Filtration options

Reverse osmosis or 4-stage carbon filtration

Storage capacity

Cold tank: ~ 2.2 gal

Hot tank: ~ 1.1 gal

Rated Voltage / Frequency

110V/60Hz

Water temperatures settings

Adjustable Cold Settings: 37°F/41°F/44°F

Default Hot Setting: 185° F

Dispensing method


Capacitive touch sensor

Purification process*



Sediment Filter

Reduces particles such as dirt, silt, rust, and pipe residue.



Pre-carbon Filter

Reduces chlorine and chemicals.



Reverse Osmosis Membrane

Reduces dissolved solids, pharmaceuticals, and metals.



Mineral Add-Back Filter

Adds minerals, electrolytes, and enhances alkalinity.



Post-carbon Filter

Final polishing filter ensures great taste.

*Also available in 4-stage Carbon Filtration: Sediment Filter, Pre-Carbon Filter, Lead/Cyst CBC Filter, and Post-Carbon Filter.

Contact us today

Waterlogic Commercial Products


www.waterlogicdealers.com

(800) 288-1891

customerservice@waterlogicausa.com

3175 Bass Pro Drive
Grapevine, TX 76051

Tested and certified



The Waterlogic WL50 is certified by IAPMO R&T against NSF/ANSI/CAN 61: Qs1, NSF/ANSI-372, and CSA B483.1 for the specific performance claims as verified and substantiated by test data. The Waterlogic WL50 is also certified to NSF/ANSI-53 for the reduction of lead and cysts and NSF/ANSI-42 for the reduction of Chlorine and Taste & Odor when using the Waterlogic WLLR-12 filter.